

# Information on ingredients Green Building Product Information (LEED®) illbruck FA880

Arkel, 05. jun 2018

To Whom It May Concern:

tremco illbruck, as an organization, is committed to quality, responsive to both internal and external customers, our employees, our community and environment, and we will treat all with respect and good stewardship.

## **Material Manufacturing Location**

illbruck FA880 is manufactured in Traunreut, Germany. If Traunreut falls within a 500 straight-line miles of the project site, the product is considered to be a locally produced material and can help contribute earning Material & Resources Credit.

### **Raw Material Extraction Information**

No single extracted material is used to produce the majority of this product. Additionally, some raw materials come from one of several sources which in-turn come from one of several raw material feed stocks. As such, point source for the raw materials cannot be determined.

## **Rapidly Renewable Raw Material Information**

The rapidly renewable material content is 0 % w/w.

#### **Recycled Content Information**

The recycled content is 0 % w/w.

#### **VOC Content Information**

illbruck FA880 has a VOC<sup>2</sup> content<sup>1</sup> of 0,1 g/L (0,01 wt%) and therefore satisfies the LEED criteria for Indoor Environmental Quality (SCAQMD Rule #1168, IEQ 4.1 Adhesives & Sealants).

#### **Pre-consumer Recycled Content Information**

All sizes 0% w/w.

## **Post-consumer Recycled Content Information**

All sizes 0% w/w.

Should you have any questions or require additional information, please do not hesitate to contact Technical Services.

Sincerely,

Kerry Knowles European Group Regulatory Manager Jacob Jan Tuinstra SDS Specialist



<sup>1</sup> "VOC content" means the mass of volatile organic compounds, expressed in grams/litre (g/L), in the formulation

of the product in its ready to use condition

<sup>2</sup> "volatile organic compound" (VOC) means any organic compound having an initial boiling point less than or equal to 250°C measured at a standard pressure of 101.3 kPa and can do damage to visual or audible senses